ViewSonic®

PJ750 Projector

Ultra-Portable Series

- **High-brightness 2,200 lumen portable projector**
- **Native 1024x768 XGA resolution**
- **Easy set-up and auto tuning**
  One-touch setup button for fast, easy sync and sharp focus.
- **Eco-mode operations**
  Eco-mode for energy savings and whisper quiet noise levels.
- **Component video for enhanced video quality**
  View HDTV signals and other video signals at maximum performance levels.
- **Ultimate flexibility with multiple-computer inputs**
  Connect two computers simultaneously for dynamic meetings.
- **Three-year limited warranty**
- **User-replaceable extended-life lamp**
  Extended lamp life beyond 2,000 hours.[2]

PJ750 high-brightness, XGA projector

The ViewSonic PJ750 delivers exceptionally bright presentations. With 2,200 lumens, 1024x768 XGA resolution and high contrast, this projector delivers clear, crisp images, even in well-lit rooms. Easy to use, the full-featured PJ750 offers zoom and digital keystone correction as well as multiple computer and video inputs and outputs for greater flexibility. Eco-mode will make the most out of your investment by extending the lamp life and reducing noise output to whisper quiet levels. Its versatility makes it an excellent choice for conference rooms, boardrooms and lecture halls. Using the PJ750 will make you confident you'll present a positive image anytime, anywhere.

ViewSonic®
See the difference.®

www.ViewSonicEurope.com

ViewSonic®

PJ750 Projector

PORTABLE HIGH-BRIGHTNESS PROJECTOR

LCD	**Type**	0.9" Polysilicon (x3) stripe pixel TFT active matrix
	Pixel Format	1024 horizontal x 768 vertical
	Lens	Manual zoom/focus (1:1.3x)
DISPLAY	**Size**	30" to 300" (measured diagonally)
	Throw Distance	1.2m to 15.7m (3.9' - 51.0')
	Lamp	200W UHB compact, 2,000+ hour rating[2]
	Brightness	2,200 lumens
	Contrast Ratio	350:1
AUDIO	**Speakers**	Stereo
	Power	1Wx2
INPUT SIGNAL	**Video**	RGB analogue, NTSC, PAL-M, PAL-N, SECAM, HDTV
	Sync	Separated and composite
	Frequency	Fh:15-80kHz; Fv:56-120Hz
COMPATIBILITY	**PC**	From SVGA up to SXGA
	MAC®[1]	Up to SXGA
CONNECTOR	**RGB Input**	15-pin HD, D-sub (x2)
	RGB Output	15-pin HD, D-sub (x1)
	Composite Video	RCA (x1)
	Component Video	RCA (x3)
	S-Video	Mini-Din 4 pin (x1)
	Audio (In/Out)	In RCA (x2) and 3.5mm (x2); out 3.5mm (x1)
	Controls	15-pin D-sub (x1)
	USB	USB upstream (x1) available through RS232 port
POWER	**Voltage**	90-132 VAC/198-264 VAC
	Frequency	50-60Hz (universal)
	Consumption	290W (typ)
USER CONTROLS	**Basic**	Standby on/off, menu (left, right, up, down), input, reset, mute, keystone, indicator (lamp, power, temp)
	Remote	Standby on/off, video, laser, blank, RGB, disk pad, auto, mouse, menu, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer
	OnView®	Brightness, contrast, V. position, H. position, H. phase, H. size, colour balance (red), colour balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu colour, timer, language, auto off, sync on green
OPERATING CONDITIONS	**Temperature**	32º F to 95º F (0º C to 35º C)
	Humidity	10% to 85% (non-condensing)
DIMENSIONS	**Physical**	298mm (W) x 228mm (D) x 76mm (H)
WEIGHT	**Net**	3.25 kg (7.2lbs.)
REGULATIONS		UL, FCC-B, c-UL, CE, CB Report, TÜV/GS, VCCI, BSMI, PCT
OTHER		Mirror reverse image, upside down image, digital keystone correction, DDC 1/2B
WARRANTY		Three-year limited warranty (lamp: 90 days)

• Digital keystone correction
Squares up the picture when projecting at an angle.

• RGB-out capability
Allows you to view your presentation on a monitor, too.

• User-replaceable extended-life lamp
Extended lamp life beyond 2,000 hours.[2]

• Accessories expand your options
ViewSonic has a wide variety of accessories for your projector including spare lamps, carrying cases, remote controls and ceiling mounts. For a complete accessories list, visit ViewSonicEurope.com.

ISO 9001 FM 40187 ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic®
See the difference.®

www.ViewSonicEurope.com

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux Tel: +33 (0) 1 41 47 49 00
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (9) 54 06 40 70
ViewSonic Italy Tel: +39 0289 079 340
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1]Adapter may be required.. [2]Running eco-mode extends life beyond 2,000 hours if proper care of lamp is taken. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. Copyright © 2003 ViewSonic Corporation. All rights reserved. PJ750-2-11/03-UK